



COLLOID ENVIRONMENTAL TECHNOLOGIES COMPANY

1350 West Shore Drive, Arlington Heights IL 60004-1440, USA
Tel: (847)392-5800 Fax: (847)506-6150

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29CFR 1910.1200
Standard must be consulted for specific requirements

8750/8751

Page 1 of 1

PRODUCT NAME: CETCOAT

Section I CHEMICAL PRODUCT AND COMPANY DATA

PRODUCT:
CHEMICAL FAMILY:
REVISION DATE:
MANUFACTURER:
CETCO
1350 West Shore Drive
Arlington Heights, IL 60004

CETCOAT
Waterproof Compound
06 /2002

Telephone Number for Information: 847-392-5800
EMERGENCY CONTACT: CHEMTREC 800-424-9300
Date Prepared: June 2002

Section II COMPOSITION/INFORMATION ON INGREDIENTS

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200)

EXPOSURE LIMITS

Ingredient	CAS. No.	TLV	STEL	PEL	Content
Portland Cement	65997-15-1	10mg/m ³	N/E	5mg/m ³	>25%
Cristalline Silica	14808-60-7	.05mg/m ³	N/E	10mg/m ³	>20%
Trade Secret	*	N/E	N/E	N/E	<20%
Titanium Dioxide	13463-67-7	10mg/ m ³	N/E	6mg/m ³	<5%

- The specific chemical identify is being withheld as a trade secret in accordance with CFR 1910.1200(I).

N/A: Not available

N/E: Not established

Section III HAZARDS IDENTIFICATION

HMIS Hazard Rating No. 2 (Moderate)

PRIMARY ROUTE OF ENTRY: *INHALATION, DERMAL, EYES*

EFFECTS OF OVER EXPOSURE:

Inhalation:	Breathing dust may cause nose, throat or lung irritation and choking.
Eyes:	May cause eye irritation, severe burns and damage to the cornea.
Skin Contact:	May cause dry skin, redness, discomfort, irritation or severe burns. May produce allergic reaction. Thickening of the skin (scleroderma) may be associated with exposure of high levels of crystalline silica.
Skin Absorption:	No known information available.
Ingestion:	Ingestion of large amounts may cause intestinal distress.