

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Ardex WPM 122

### SYNONYMS

"bitumen based polyethylene membrane", "Shelterbit HD Bridge Membrane"

### PRODUCT USE

Used as a waterproofing membrane.

### SUPPLIER

Company: Ardex Australia Pty Ltd

Address:

20 Powers Road

Seven Hills






NSW, 2147

AUS

Telephone: 1800 224 070

Fax: +61 2 9838 7817

### HAZARD RATINGS

		Min	Max	
Flammability:	1			
Toxicity:	2			
Body Contact:	2			
Reactivity:	1			
Chronic:	2			

Min/Nil=0  
Low=1  
Moderate=2  
High=3  
Extreme=4

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.**

### POISONS SCHEDULE

None

#### RISK

- Vapours may cause drowsiness and dizziness.
- Inhalation and/or ingestion may produce health damage\*.
- Cumulative effects may result following exposure\*.
- May produce discomfort of the eyes respiratory tract and skin\*.
- Possible skin sensitiser\*.
- Repeated exposure potentially causes skin dryness and cracking\*.

\* (limited evidence).

#### SAFETY

- Avoid contact with skin.
- Wear eye/ face protection.
- Use only in well ventilated areas.
- Keep container in a well ventilated place.
- In case of contact with eyes rinse with plenty of water and contact Doctor or Poisons Information Centre.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
bitumen (petroleum)	8052-42-4	>60
polyethylene	9002-88-4	<10
No other ingredients disclosed by Manufacturer.		

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- 
- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- 
- Immediately drench burn area in cold running water.
- If hot bitumen adheres to the skin, DO NOT attempt to remove it (it acts as a sterile dressing).
- For burns to the head and neck and trunk, apply cold wet towels to the burn area, and change frequently to maintain cooling.
- Cooling should be maintained for no longer than thirty minutes.
- When hot bitumen completely encircles a limb, it may have a tourniquet effect and should be split as it cools.
- Transport to hospital or doctor.

In case of burns:

- Immediately apply cold water to burn either by immersion or wrapping with saturated clean cloth.
- DO NOT remove or cut away clothing over burnt areas. DO NOT pull away clothing which has adhered to the skin as this can cause further injury.
- DO NOT break blister or remove solidified material.
- Quickly cover wound with dressing or clean cloth to help prevent infection and to ease pain.
- For large burns, sheets, towels or pillow slips are ideal; leave holes for eyes, nose and mouth.
- DO NOT apply ointments, oils, butter, etc. to a burn under any circumstances.
- Water may be given in small quantities if the person is conscious.
- Alcohol is not to be given under any circumstances.
- Reassure.
- Treat for shock by keeping the person warm and in a lying position.
- Seek medical aid and advise medical personnel in advance of the cause and extent of the injury and the estimated time of arrival of the patient.

### INHALED

- 
- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

### NOTES TO PHYSICIAN

- Treat symptomatically.

Burns : No attempt should be made to remove the bitumen (it acts as a sterile dressing). Cover the bitumen with tulle gras and leave for two days when any detached bitumen can be removed. Re-dress and leave for a further week. If necessary refer to a burns unit. [Manufacturer].

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- 
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

### FIRE FIGHTING

- 
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

## **FIRE/EXPLOSION HAZARD**

- 
- Hot organic vapours or mist are capable of sudden spontaneous combustion when mixed with air even at temperatures below their published autoignition temperatures.
- The temperature of ignition decreases with increasing vapour volume and vapour/air contact times and is influenced by pressure change.
- Ignition may occur under elevated-temperature process conditions especially in processes performed under vacuum subjected to sudden ingress of air or in processes performed at elevated pressure, where sudden escape of vapours or mists to the atmosphere occurs.
- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include:.

carbon dioxide (CO<sub>2</sub>).

formaldehyde.

other pyrolysis products typical of burning organic material.

NOTE: Burns with intense heat. Produces melting, flowing, burning liquid and dense acrid black smoke.

May emit poisonous fumes.

May emit corrosive fumes.

CARE: Contamination of heated / molten liquid with water may cause violent steam explosion, with scattering of hot contents.

## **FIRE INCOMPATIBILITY**

- 
- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

## **HAZCHEM**

None

## **Personal Protective Equipment**

Gas tight chemical resistant suit.

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

### **EMERGENCY PROCEDURES**

#### **MINOR SPILLS**

- 
- Clean up all spills immediately.
- Secure load if safe to do so.
- Bundle/collect recoverable product.
- Collect remaining material in containers with covers for disposal.

#### **MAJOR SPILLS**

- 
- Clean up all spills immediately.
- Wear protective clothing, safety glasses, dust mask, gloves.
- Secure load if safe to do so. Bundle/collect recoverable product.
- Use dry clean up procedures and avoid generating dust.
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Water may be used to prevent dusting.
- Collect remaining material in containers with covers for disposal.
- Flush spill area with water.

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

## **Section 7 - HANDLING AND STORAGE**

### **PROCEDURE FOR HANDLING**

- 
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

## SUITABLE CONTAINER

- 
- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

## STORAGE INCOMPATIBILITY

- 
- Avoid reaction with oxidising agents

## STORAGE REQUIREMENTS

- 
- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



X: Must not be stored together

O: May be stored together with specific precautions

+: May be stored together

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Australia Exposure Standards	bitumen (petroleum) (Bitumen fumes)		5						
The following materials had no OELs on our records									
● polyethylene: CAS:9002-88-4									

### MATERIAL DATA

ARDEX WPM 122:

Not available

BITUMEN (PETROLEUM):

■ bitumen (asphalt) fumes [8052-42-4]

TLV\* TWA: 0.5 mg/m<sup>3</sup> A4 asphalt (petroleum, bitumen) fume, as benzene soluble aerosol

ES\* TWA: 5 mg/m<sup>3</sup> as fumes

OES\* TWA: 5 mg/m<sup>3</sup>; STEL: 10 mg/m<sup>3</sup> as fumes

Based on surveys of asphalt workers in oil refineries and in the roofing industry the TLV-TWA is thought to reduce the risk of possible carcinogenicity.

Odour Threshold Value for hydrogen sulfide: 0.0011 ppm (detection), 0.0045 ppm (recognition)

NOTE: Detector tubes for hydrogen sulfide, measuring in excess of 0.5 ppm are available commercially.

The TLV-TWA is protective against sudden death, eye irritation, neurasthenic symptoms such as fatigue, headache, dizziness, and

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

irritability, or permanent central nervous system effects that may result from acute, subchronic, or acute exposure to hydrogen sulfide. The offensive odour of hydrogen sulfide does not give a reliable warning signal because olfactory fatigue occurs at concentrations of 150 to 200 ppm.

Hydrogen sulfide is probably the leading cause of sudden death in the workplace. Lethal hydrogen sulfide toxicity following inhalation of 1000-2000 ppm paralyses the respiratory centre and causes breathing to stop. At concentrations between 500 to 1000 ppm, the carotid bodies are stimulated causing hypernea which is followed by apnea. Low concentrations (50-1500 ppm) produce eye and respiratory tract irritation. Prolonged exposure to concentrations of the order of 250-500 ppm may produce pulmonary oedema although 50 ppm has also reportedly produced this effect.

Concentrations in excess of 50 ppm produce acute conjunctivitis with pain, lachrymation and photophobia. These acute changes may progress to keratoconjunctivitis and vesiculation of the corneal epithelium.

Concentrations between 5 and 30 ppm produce ocular toxicity.

Odour Safety Factor(OSF)

OSF=1.2E3 (HYDROGEN SULFIDE).

## PERSONAL PROTECTION



### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]

### HANDS/FEET

- When handling hot materials wear heat resistant, elbow length gloves.
- Rubber gloves are not recommended when handling hot objects, materials
- Protective gloves eg. Leather gloves or gloves with Leather facing
- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber

#### NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

### OTHER

- Usually handled as molten liquid which requires worker thermal protection and increases hazard of vapour exposure.
- CAUTION: Vapours may be irritating.
- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

### RESPIRATOR

- Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half-face Respirator	Full-Face Respirator
1000	10	A-AUS P	-
1000	50	-	A-AUS P
5000	50	Airline *	-
5000	100	-	A-2 P
10000	100	-	A-3 P
	100+		Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

**ARDEX WPM 122****Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

■ Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

Air Speed:

solvent, vapours, degreasing etc., evaporating from tank (in still air). 0.25-0.5 m/s (50-100 f/min.)

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) 0.5-1 m/s (100-200 f/min.)

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) 1-2.5 m/s (200-500 f/min.)

grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion) 2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

Upper end of the range

1: Room air currents minimal or favourable to capture

1: Disturbing room air currents

2: Contaminants of low toxicity or of nuisance value only.

2: Contaminants of high toxicity

3: Intermittent, low production.

3: High production, heavy use

4: Large hood or large air mass in motion

4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

**Section 9 - PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE**

Black membrane sheet with a bitumen base; insoluble in water.

**PHYSICAL PROPERTIES**

Does not mix with water.

Sinks in water.

Molecular Weight: Not Applicable	Boiling Range (°C): 470 (bitumen)	Melting Range (°C): >1100
Specific Gravity (water=1): 1-1.5	Solubility in water (g/L): Immiscible	pH (as supplied): Not Applicable
pH (1% solution): Not Applicable	Vapour Pressure (kPa): Not Applicable	Volatile Component (%vol): Not Applicable
Evaporation Rate: Not Available	Relative Vapour Density (air=1): Not Applicable	Flash Point (°C): 230 (bitumen)
Lower Explosive Limit (%): Not Applicable	Upper Explosive Limit (%): Not Applicable	Autoignition Temp (°C): 1485 (bitumen)
Decomposition Temp (°C): Not Available	State: Manufactured	Viscosity: Not Applicable

**Section 10 - CHEMICAL STABILITY****CONDITIONS CONTRIBUTING TO INSTABILITY**

■ Product is considered stable and hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

**Section 11 - TOXICOLOGICAL INFORMATION****POTENTIAL HEALTH EFFECTS****ACUTE HEALTH EFFECTS****SWALLOWED**

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

**EYE**

■ There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

Workers exposed to fumes of blown bitumens developed inflammation of the cornea and conjunctiva.

**SKIN**

■ There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

**INHALED**

■ Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Hydrogen sulfide poisoning can cause increased secretion of saliva, nausea, vomiting, diarrhoea, giddiness, headache, vertigo, memory loss, palpitations, heartbeat irregularities, weakness, muscle cramps, confusion, sudden collapse, unconsciousness and death due to paralysis of breathing (at levels above 300 parts per million). The "rotten egg" odour is not a good indicator of exposure since odour fatigue occurs and odour is lost at over 200 ppm. The gas can enter the body through a punctured ear drum and even when wearing some respiratory protection. Immediate supportive care is essential. Ensure medical help is addressed as part of the site emergency plan and that employees who may be accidentally exposed are made aware of the existence of such a plan.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Acute exposure to bitumen/asphalt vapours may cause coughing, chest tightness, muscle weakness, dizziness, tiredness, poor concentration, and even nausea and vomiting. Workers exposed to hot blown bitumens show bronchitis, inflammation of the nose, mouth, pharynx and larynx; symptoms include cough, phlegm, burning of the throat and chest, hoarseness, headache and nasal discharge. Animals exposed to blown bitumen fumes, aerosols and smoke, developed patchy regions of emphysema, dilation of bronchioles, lung inflammation, and severe localized bronchitis, as well as abscess formation and necrosis. Concentrations of asphalt in the workplace ranges from virtually zero in areas of good mechanical ventilation to 40 mg/m<sup>3</sup> where there is very poor natural draft. Generally conditions are only considered satisfactory where the concentration is less than 10 mg/m<sup>3</sup>.

Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C<sub>2</sub>-C<sub>12</sub>) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor. Massive exposures can lead to severe central nervous system depression, deep coma and death. Convulsions can occur due to brain irritation and/or lack of oxygen. Permanent scarring may occur, with epileptic seizures and brain bleeds occurring months after exposure. Respiratory system effects include inflammation of the lungs with oedema and bleeding. Lighter species mainly cause kidney and nerve damage; the heavier paraffins and olefins are especially irritant to the respiratory system. Alkenes produce pulmonary oedema at high concentrations. Liquid paraffins may produce sensation loss and depressant actions leading to weakness, dizziness, slow and shallow respiration, unconsciousness, convulsions and death. C<sub>5</sub>-7 paraffins may also produce multiple nerve damage. Aromatic hydrocarbons accumulate in lipid rich tissues (typically the brain, spinal cord and peripheral nerves) and may produce functional impairment manifested by nonspecific symptoms such as nausea, weakness, fatigue, vertigo; severe exposures may produce inebriation or unconsciousness. Many of the petroleum hydrocarbons can sensitise the heart and may cause ventricular fibrillation, leading to death.

**CHRONIC HEALTH EFFECTS**

■ Long term low level exposure to hydrogen sulfide may produce headache, fatigue, dizziness, irritability and loss of sexual desire.

These symptoms may also result when exposed to hydrogen sulfide at high concentration for a short period of time.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

**TOXICITY AND IRRITATION**

■ Not available. Refer to individual constituents.

**BITUMEN (PETROLEUM):**

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

**POLYETHYLENE:**

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

**TOXICITY****IRRITATION**

**ARDEX WPM 122****Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

Oral (rat) LD50: 3000 mg/kg

Inhalation (mouse) LC50: 12000 mg/m<sup>3</sup>/30m

■ The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

polyethylene pyrolyzate

**CARCINOGEN**

Bitumens, extracts of steam-refined and air-refined	International Agency for Research on Cancer (IARC) Carcinogens	Group 2B
Bitumens, steam-refined, cracking-residue and air-refined	International Agency for Research on Cancer (IARC) Carcinogens	Group 3
Polyethylene	International Agency for Research on Cancer (IARC) Carcinogens	Group 3

**Section 12 - ECOLOGICAL INFORMATION**

■ DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

ARDEX WPM 122:

BITUMEN (PETROLEUM):

■ for bitumens/ asphalts:

This family of hydrocarbon is expected to have similar boiling points, vapor pressures, log Kow values (>10), and water solubilities. Limited environmental fate data also support the grouping of bitumens/ asphalts under one category. Bitumen/ asphalts contain complex hydrocarbon mixtures with molecular weights ranging from 500-2000 and carbon numbers predominantly higher than C25, vapor pressures are negligible. The high molecular weights and similar hydrocarbon distributions among the bitumens/ asphalts support the conclusion that the toxicity of this group, in general, is not expected to vary significantly across members.

Environmental fate:

Upon release to the environment, bitumens/ asphalts are expected to distribute similarly because of their low volatility and limited water solubility. Bitumen/ asphalts are expected to be resistant to biodegradation, and those components that are soluble in water are expected to be resistant to hydrolysis. When bitumen/ asphalts are heated to facilitate paving or roofing applications, the lighter, more volatile components are distilled into the atmosphere. They condense as they cool, forming small droplets of liquid known as bitumen or asphalt fume condensate. The majority of hydrocarbons in bitumen/ asphalts are not susceptible to direct photolysis, since they do not have functional groups that absorb sunlight greater than 290 nm. However, certain aromatic and unsaturated compound members have the potential to undergo photolysis because they absorb light in the environmental UV region. Since bitumens/ asphalts contain high molecular weight hydrocarbons, partitioning to the atmosphere is not considered to be important.

When compositionally analysing bitumens/ asphalts for certain toxicity endpoints the percentage of 3- to 7-ring polyaromatic hydrocarbons (PAHs) is important. The levels of 3- to 7-ring PAHs are expected to be low considering the processes used to manufacture these substances. Fumes generated experimentally at high temperatures are more likely to contain carcinogenic PAHs than fumes generated at the lower temperatures usually seen in field samples. Therefore, generating conditions are expected to significantly affect toxicity.

Ecotoxicity:

Bitumens/ asphalts by analogy with other high molecular weight hydrocarbons are not likely to show adverse acute or chronic ecological effects in aquatic species.

■ For hydrocarbons:

Environmental fate:

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some hydrocarbon will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions hydrocarbons degrade to water and carbon dioxide, while under anaerobic processes they produce water, methane and carbon dioxide.

Alkenes have low log octanol/water partition coefficients (Kow) of about 1 and estimated bioconcentration factors (BCF) of about 10; aromatics have intermediate values (log Kow values of 2-3 and BCF values of 20-200), while C5 and greater alkanes have fairly high values (log Kow values of about 3-4.5 and BCF values of 100-1,500).

The estimated volatilisation half-lives for alkanes and benzene, toluene, ethylbenzene, xylene (BTEX) components were predicted as 7 days in ponds, 1.5 days in rivers, and 6 days in lakes. The volatilisation rate of naphthalene and its substituted derivatives were estimated to be slower.

Indigenous microbes found in many natural settings (e.g., soils, groundwater, ponds) have been shown to be capable of degrading organic compounds. Unlike other fate processes that disperse contaminants in the environment, biodegradation can eliminate the contaminants without transferring them across media.

The final products of microbial degradation are carbon dioxide, water, and microbial biomass. The rate of hydrocarbon degradation depends on the chemical composition of the product released to the environment as well as site-specific environmental factors. Generally the straight chain hydrocarbons and the aromatics are degraded more readily than the highly branched aliphatic compounds. The n-alkanes, n-alkyl aromatics, and the aromatics in the C10-C22 range are the most readily biodegradable; n-



# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

alkanes, n-alkyl aromatics, and aromatics in the C5-C9 range are biodegradable at low concentrations by some microorganisms, but are generally preferentially removed by volatilisation and thus are unavailable in most environments; n-alkanes in the C1-C4 ranges are biodegradable only by a narrow range of specialised hydrocarbon degraders; and n-alkanes, n-alkyl aromatics, and aromatics above C22 are generally not available to degrading microorganisms. Hydrocarbons with condensed ring structures, such as PAHs with four or more rings, have been shown to be relatively resistant to biodegradation. PAHs with only 2 or 3 rings (e.g., naphthalene, anthracene) are more easily biodegraded. In almost all cases, the presence of oxygen is essential for effective biodegradation of oil. The ideal pH range to promote biodegradation is close to neutral (6-8). For most species, the optimal pH is slightly alkaline, that is, greater than 7.

All biological transformations are affected by temperature. Generally, as the temperature increases, biological activity tends to increase up to a temperature where enzyme denaturation occurs.

Atmospheric fate: Alkanes, isoalkanes, and cycloalkanes have half-lives on the order of 1-10 days, whereas alkenes, cycloalkenes, and substituted benzenes have half-lives of 1 day or less. Photochemical oxidation products include aldehydes, hydroxy compounds, nitro compounds, and peroxyacyl nitrates. Alkenes, certain substituted aromatics, and naphthalene are potentially susceptible to direct photolysis.

#### Ecotoxicity:

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

The values of log Kow for individual hydrocarbons increase with increasing carbon number within homologous series of generic types. Quantitative structure activity relationships (QSAR), relating log Kow values of single hydrocarbons to toxicity, show that water solubility decreases more rapidly with increasing Kow than does the concentration causing effects. This relationship varies somewhat with species of hydrocarbon, but it follows that there is a log Kow limit for hydrocarbons, above which, they will not exhibit acute toxicity; this limit is at a log Kow value of about 4 to 5. It has been confirmed experimentally that for fish and invertebrates, paraffinic hydrocarbons with a carbon number of 10 or higher (log Kow >5) show no acute toxicity and that alkylbenzenes with a carbon number of 14 or greater (log Kow >5) similarly show no acute toxicity. QSAR equations for chronic toxicity also suggest that there should be a point where hydrocarbons with high log Kow values become so insoluble in water that they will not cause chronic toxicity, that is, that there is also a solubility cut-off for chronic toxicity. Thus, paraffinic hydrocarbons with carbon numbers of greater than 14 (log Kow >7.3) should show no measurable chronic toxicity.

■ Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

■ For hydrogen sulfide:

#### Environmental fate:

Since hydrogen sulfide exists as a gas at atmospheric pressure, partitioning to the air is likely to occur after environmental releases. However, the compound is also soluble in oil and water, and therefore, may partition as well to surface water, groundwater, or moist soil. In addition, sorption of hydrogen sulfide from air onto soil and plant foliage occurs. Hydrogen sulfide's solubility in pure water varies with temperature from 5.3 g/L at 10 °C to 3.2 g/L at 30 °C. Once hydrogen sulfide is dissolved in water, it will dissociate into bisulfide ion (HS-) and sulfide ion (S2-); the ratio of the concentrations of these various ions will depend on the pH of the solution. Hydrogen sulfide can also form insoluble sulfide salts with various metals (i.e., copper, zinc, nickel, and iron) that may be present in soils or environmental waters.

Hydrogen sulfide evaporates easily from water, and the rate of evaporation depends on factors such as temperature, humidity, pKa, pH, and the concentration of certain metal ions. Hydrogen sulfide will cross the air-water interface with kinetics similar to other unreactive gases, such as oxygen (O2), nitrogen (N2), and carbon dioxide (CO2), at pHs ≤6. At higher pHs, such as seawater, which has a pH of 8 or greater, hydrogen sulfide escape is enhanced due to an ionic species gradient in the water close to the surface. Complexation of bisulfide and sulfide ions to trace metal ions (i.e., Zn2+, Co2+, and Ni2+) found in seawater will also have an effect on the transport of hydrogen sulfide across the air-water interface.

Clay or organic matter may sorb hydrogen sulfide. Under natural conditions, it is likely that some of the hydrogen sulfide would be oxidized to sulfate, which may be removed by leaching or taken up by plants. This, in turn, may make gas sorption sites available for additional sorption. Several species of soil, aquatic, and marine microorganisms oxidize hydrogen sulfide to elemental sulfur, and its half-time in these environments usually ranges from 1 hour to several hours. Food chain bioconcentration and biomagnification are unlikely.

In the atmosphere, hydrogen sulfide may be oxidized by oxygen (O2) and ozone (O3) to give sulfur dioxide (SO2), and ultimately sulfate compounds. Sulfur dioxide and sulfates are eventually removed from the atmosphere through absorption by plants, deposition on and sorption by soils, or through precipitation. A residence time of approximately 1.7 days at an ozone concentration of 0.05 mg/m3 has been calculated for hydrogen sulfide. The effective life-times for hydrogen sulfide based on summer daytime and yearly average hydroxyl radical concentrations have been estimated to be 0.23 and 2.3 days, respectively, based a measured rate constant of 4.8x10-12 cm3/molecule second. Life-times in air ranging from approximately 1 day in the summer to 42 days in the winter have been estimated for hydrogen sulfide. Hydrogen sulfide is not expected to be decomposed by direct absorption of ultraviolet radiation and the reaction with ozone is not expected to be a significant environmental fate.

In aqueous solution, hydrogen sulfide is a weak acid, exhibiting two acid dissociation constants. The first dissociation yields bisulfide ion (HS-), and the second yields sulfide ion (S2-), with pKa values for each of these dissociations of 7.04 and 11.96, respectively. At a pH of 7.0, the ratio of the concentration of aqueous hydrogen sulfide to bisulfate ion is approximately 1-to-1. As the pH increases above 7.0, the ratio of the concentration of bisulfide ion to aqueous hydrogen sulfide increases. At a pH of 8, the ratio of the concentration of bisulfide ion to the concentration of aqueous hydrogen sulfide is approximately 10-to-1. The relative concentration of sulfide ion does not begin to increase until a pH of 11 is exceeded; only above pH 12 will the concentration of sulfide ion become significant (>50%). Hydrogen sulfide oxidation by O2 readily occurs in surface waters. At 25 °C and pH 8, half-times of 50 and 26 hours were reported for hydrogen sulfide in water and seawater, respectively. Above pH 8, however, the rate of oxidation was independent of pH.

Hydrogen sulfide in waste water may be controlled by addition of oxidizing chemicals, which react to form less toxic byproducts. In warm, damp environments (such as manholes and gravity sewers), hydrogen sulfide may be oxidized by autotrophic bacteria to sulfuric acid. Chemical oxidation of hydrogen sulfide dissolved in sewage water produces sulfur at pH 6-7, while sulfur, polysulfides, thiosulfates, and ultimately sulfate are formed at pHs of 7-9.

Hydrogen sulfide is one of the principal components in the natural sulfur cycle. Bacteria, fungi, and actinomycetes (a fungus-like bacteria) release hydrogen sulfide during the decomposition of sulfur containing proteins and by the direct reduction of sulfate (SO42-). Hydrogen sulfide is also consumed by bacteria found in soil and water that oxidize hydrogen sulfide to elemental sulfur. Photosynthetic bacteria can oxidize hydrogen sulfide to sulfur and sulfate in the presence of light and the absence of oxygen.

A number of microorganisms have been found to degrade hydrogen sulfide to elemental sulfur or sulfate. Among these are a heterotrophic bacterium of the genus Xanthomonas isolated from dimethyl disulfide-acclimated peat, heterotrophic fungi, and a marine isopod. Soils may sorb considerable amounts of hydrogen sulfide from the air, retaining most of it in the form of elemental sulfur. Manganese compound found in these soils appeared to catalyze the oxidation of hydrogen sulfide to elemental sulfur

# ARDEX WPM 122

**Hazard Alert Code:**  
**MODERATE**

Chemwatch Material Safety Data Sheet

Revision No: 4

Chemwatch 5042-78

Issue Date: 1-Nov-2008

CD 2009/3

Ecotoxicity:  
Fish LC50 (96 h): 075->0.4 mg/l.  
POLYETHYLENE:

## Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Ardex WPM 122 bitumen (petroleum) polyethylene		No data  No data No data		

## Section 13 - DISPOSAL CONSIDERATIONS

- 
- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

## Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

## Section 15 - REGULATORY INFORMATION

### POISONS SCHEDULE

None

### REGULATIONS

Regulations for ingredients

**bitumen (petroleum) (CAS: 8052-42-4) is found on the following regulatory lists;**

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) Carcinogens", "OECD Representative List of High Production Volume (HPV) Chemicals"

**polyethylene (CAS: 9002-88-4) is found on the following regulatory lists;**

"Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) Carcinogens"

**No data for Ardex WPM 122 (CW: 5042-78)**

## Section 16 - OTHER INFORMATION

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 1-Nov-2008

Print Date: 4-Nov-2009