

Duo Primer

Solvent-base bitumen primer

Product Description:

Duo Primer is a solvent-base bitumen coating. It may be used on a dry and porous surface.

Uses:

Easily applied surface conditioning primer to use before welding or gluing of all types of De Boer modified bitumen membranes.

Characteristics:

Flashpoint:	min 40°C (Pensky-Martens)
Viscosity at 20°C :	+/- 25°C Engler
Specific gravity:	+/- 0.9 kg/l (at 20°C)
Drying time:	3-5 hours (depending on weather conditions.)
Toxicity:	solvents used meet the agreement of the Belgium Labour Protection Regulations (art. 393+ 394 R.G.P.T.)

Directions For Use:

Duo Primer is ready for use, applicable with spray equipment or by roller on clean surfaces.

Application Rate:

4 to 5 sqm/litre (on porous surfaces)
6 to 7 sqm/litre (on non-porous surfaces)

Cleaning:

Clean equipment with White Spirits or Mineral Turpentine immediately after use.

Packaging:

4 litre and 25 litre pails

Components:

Bitumen + solvent (white spirit).

Storage:

Store pails in a dry place always in upright position, out of direct sunlight. Do not store Duo Primer in the neighbourhood of open flames, because of its solvent content.

Transport Classifications:

IMDG Class 3.3
UN No. 1999



Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz

© Equus Industries Ltd
Edition 4
February 2017