



## MATERIAL INFORMATION DATA SHEET

# Trowel 2mm & 3mm

### DESCRIPTION

**Euromix® Trowel** is a durable, high build acrylic texture coating system. **Euromix® Trowel** is trowel applied to produce a scratch coat in either a vertical or circular pattern, and incorporates a top coat of Euromix® Flex.

### USES

**Euromix® Trowel** is used to enhance, restore and protect a wide range of building structures where an attractive Mediterranean style is desired for both interior and exterior applications.

### FEATURES – BENEFITS

- **Euromix® Trowel** is suitable for both commercial and residential structures for interior and exterior applications.
- Both grades can be finished in either a vertical scratch or circular pattern.
- The thickness of **Euromix® Trowel** allows minor imperfections to be filled, thus minimising the degree of surface preparation.
- Can be applied directly to Autoclaved Aerated Concrete (AAC) panels without the need to skim coat with subsequent cost savings in surface preparation.
- **Euromix® Trowel** is water-based for applicator safety and ease of use.
- **Euromix® Trowel** is available in a selected range of colours and can be tinted to other manufacturers' colours.
- **Euromix® Trowel** will outlast conventional paint three-fold.

### SUBSTRATES

**Euromix® Trowel** is suitable for a wide range of substrates includes off-form concrete, tilt-up, pre-cast concrete, blocks and brickwork, Autoclaved Aerated Concrete (AAC) panels and blocks, and fibre-cement sheeting.

### COLOUR

White.

**Euromix® Trowel** can be tinted to a selected range of colours and may be matched to other manufacturers' colours.

### SURFACE PREPARATION

Surface preparation is the responsibility of the Contractor and/or Applicator. The substrate must be level and free from irregularities, and be thoroughly clean and free from any contaminants that may interfere with adhesion. Cementitious substrates should be left for 12-28 days before coating, and contain less than 15% moisture (wood equivalent) before applying the texture coating. Painted surfaces should be thoroughly washed and any loose flaking paint removed.

### MIXING

**Euromix® Trowel** should be agitated by means of an electric drill mixer before use.

### APPLICATION METHOD

**Euromix® Trowel** is trowelled on with a stainless steel trowel and finished with a polystyrene float. When dry, it is top coated with Euromix® Flex using a 12mm pile Rolana roller.

#### PRIMER

It is necessary to apply one (1) coat of Euromix® Primer to correctly prepare substrates before commencing application of the **Euromix® Trowel**.

#### GENERAL DATA

##### **Drying times:**

Surface dry: Four (4) hours

Recoat: Twenty four (24) hours

Hard dry: Seven (7) days

All figures are quoted at 25 degrees Celsius at 50% Relative Humidity

Coverage: 15 litres with cover approximately 9 square metres

Density:

Texture: Coarse texture to achieve either a vertical or circular scratch pattern.

Gloss level: Matt

Consistency: Thick plaster-like material

Adhesion: Excellent

Moisture control: Excellent

Abrasion resistance: Excellent

Shelf life: Twelve (12) months when stored properly

Clean up: Clean equipment with water

Precaution: Application of **Euromix® Trowel** should be carried out at temperatures above 10 degrees Celsius and below 35 degrees Celsius. **Euromix® Trowel** must not be subjected to hydrostatic pressure.

Packaging: 15 Litre plastic pails.

#### SAFETY

**Euromix® Trowel** is water-based, but may irritate skin or eyes. Use of gloves and goggles are recommended.

- If swallowed, do not induce vomiting. Give plenty of water to drink and seek medical advice.
- If contact with eyes, hold eyes open, flood with water for at least 15 minutes, and see a doctor if irritation occurs.
- If contact with skin, wash skin thoroughly with soap and water. Do not use solvents.

#### SPECIAL CONDITIONS

- The excellent performance of Euromix® products is dependant upon correct application and proper surface preparation. We recommend that Euromix® products be applied by applicators and trades people experienced in the application of the product chosen or specified.
- Provision of applied site sample/reference area.  
In the interest of quality control, the Applicator shall prepare an Applied Sample of the coating, onto the surface to which it is to be applied.  
The site reference enables you to satisfy yourself as to:
  - (a) Substrate preparation
  - (b) Product colour and quality
  - (c) The skill of the applicator
  - (d) The finish that you require