

# EC Material Safety Data Sheet

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH  
Product number: 168 (200/2), 185 (200/1), 193 (150/1)  
Trade name: VANDEX FLEXTAPE  
Printing date: 01.08.2006

Reviewed on: 01.08.2006

Page: 01/02

## 01. Identification of substance, preparation and company

### Trade name

VANDEX FLEXTAPE

### Use

Sealing Tape

### Manufacturer/Supplier

Vandex Isoliermittel-Gesellschaft m.b.H.  
Industriestrasse 19-23  
D-21493 Schwarzenbek  
Phone: +49 4151 89 15-0  
Fax: +49 4151 89 15 50

### \* General Information

Phone: +49 41 51 89 15 31 (Laboratory, Vandex Isoliermittel GmbH, Germany)  
Phone: +41 32 626 36 36 (Technical Department, Vandex International AG, Switzerland)

### \* Emergency telephone

GIZ Nord Poisons Centre, Germany  
Phone: +49 551 19240

## 02. Composition/Information on components

### Chemical characterization

Thermoplastic Elastomer (TPM)

### \* Hazardous components

None

## 03. Hazards identification

Not applicable

## 04. First aid measures

In direct connection with the product not applicable in practice.

## 05. Fire-fighting measures

### Extinguishing media - suitable

Water, foam, CO<sub>2</sub>

### Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

s. Pt. 10

### \* Special protective equipment for fire-fighters

Use self-contained breathing apparatus

## 06. Accidental release measures

Not applicable

## 07. Handling and storage

### Requirements to be met by storerooms and containers

Cool and dry

### Information about separation of incompatible products

Special measures are not known.

## 08. \* Exposure controls and personal protection

### Exposure limits

none

### Occupational exposure controls

not applicable

### Personal protective equipment

Normal working clothes

---

## EC Material Safety Data Sheet

Manufacturer/Supplier: Vandex Isoliermittel-Gesellschaft mbH  
Product number: 168 (200/2), 185 (200/1), 193 (150/1)  
Trade name: VANDEX FLEXTAPE  
Printing date: 01.08.2006

Reviewed on: 01.08.2006

Page: 02/02

---

### 09. Physical and chemical properties

#### Image

Form: flat tape  
Colour: grey  
Odour: without characteristic smell

### 10. Stability and reactivity

#### Conditions to avoid

Temperatures > 80 °C

#### Materials to avoid

-

#### Dangerous decomposition products

At temperatures > 200 °C and in case of fire formation of acetic acid, acrylic acid and their derivatives possible

### 11. \* Toxicological information

No data available

### 12. \* Ecological information

No negative environmental impact known when used according to product literature.

### 13. Disposal considerations

Recycling is to be preferred to disposal. The choice of disposal procedure depends upon the nature of the goods to be disposed of at the time of disposal and upon the local possibilities for disposal. Local laws and regulations, and conditions stipulated by the authorities, must be complied with in every case.

#### Product/Preparation

The product can be passed on to an appropriate incineration plan.

EWC	1702 03	plastic from construction and demolition waste
	1707 01	mixed construction and demolition waste

### 14. Transport information

Not restricted

### 15. Regulatory information

No dangerous substance, not restricted.

### 16. Other information

Alterations/supplements to the previous version are marked with \*

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---