

MATERIAL SAFETY DATA SHEET IDENTIFICATION

AQUADEX

<u>Formal Shipping Name</u>	Acrylic Pigmented Dispersion	
<u>Hazard Identification</u>	UN Number	N/A
	Hazchem Code	N/A
	Dangerous Goods	N/A
	Flash Point	N/A
	Poison Schedule	N/A
<u>Use</u>	Application by brush roller or spray to concrete and masonry products.	
<u>Chemical Constitution</u>	Compound	Proportion
	Acrylic Polymer	20-50%
	Barium Sulphate	10-20%
	Magnesium Silicate	10-20%
	Titanium Dioxide	0-10%
<u>Physical Description / Properties</u>	Appearance	Coloured Viscous Liquid
	Odour	Slight
	Percent Solids (wt)	40%
	Flash Point	N/A
	Specific Gravity	1.45
<u>Health Effects</u>	Swallowed	Not considered toxic by ingestion
	Eye	Slight irritation.
	Skin	Not irritating to the skin
	Inhalation	Not considered toxic by inhalation
<u>First Aid</u>	Seek medical advice. Notify Poison Centre Ph 0800 764 766	
	Swallowed	Do not induce vomiting. Give two glasses of milk or water.
	Eye	Irrigate continuously for 15 minutes.
	Inhalation	Remove victim to fresh air.
<u>Handling</u>	Exposure	Not considered hazardous.
<u>Personal Protection</u>	Eyes	Goggles if splashing exists.
	Skin	Nil
	Respiratory	Nil
<u>Storage and Transport</u>	Class	N/A
	Packaging Group	N/A
	Stability	Stable
<u>Spills and Disposal</u>	Absorb with sand or earth and place in suitable container for disposal.	
<u>Fire and Explosion Hazard</u>	Flammability	N/A
	Extinguishing Media	N/A
	Decomposition	N/A Does not burn.

The information contained in this Material Data Information Sheet is based on our experience and testing, and represents the latest information available at the date of production. No responsibility is taken for uses outside of the intended application. We reserve the right to update information parameters and formulations at any time without prior notice.